

REGARDING: Wiring Harness Guide for Genesis Series 110E

The Genesis Series 110E comes included with 3 wiring harness sections. A motor controller or switch is not included as we envision most of these units installed directly into the upfitter switches on the vehicle. See the guide below on a brief description of each harness section included.

1. Vehicle Harness

- a. One end of this harness has a 2 pin Deutsch connector to be mated to the small harness coming out of the pump on the sprayer.
- b. Other end of this harness has a 40 Amp Fuse in-line on the 12V Positive Ring terminal, and a 12V Negative Ring terminal. These ring terminals should be installed to the battery of the UTV. The 4 pin Deutsch plug to be mated to the Motor Pump Power Harness.

2. Motor Pump Power Harness

- a. One end of this harness has a 4 pin Deutsch plug to be mated to the Vehicle Harness.
- b. Other end of this harness has 3 ring terminals (12V Positive, 12V Negative, and Motor Signal) to be wired into the upfitter switches on the UTV or a stationary rocker switch (not included).

3. Extension Harness

- a. If the Motor Pump Power Harness itself is not long enough to reach from the sprayer to the battery of the UTV, this Extension Harness can be mated to add additional length. Connect the corresponding 2 pin Deutsch connector to the pump on the sprayer and the other 2 pin Deutsch connector to the Motor Pump Power Harness.



Should you have any questions regarding the information in this bulletin, please contact BOSS Snowplow at 888-492-6841, email us at sales@bossplow.com or chat with us via www.bossplow.com.

Thank you,

VSI by BOSS Snowplow