



**SK BOX PLOW
SPECIFICATIONS**

	SK-R 6	SK-8	SK-R 8	SK-10	SK-R 10	SK-12
MOLDBOARD						
Moldboard Width	79" (200 cm)	100" (254 cm)	102.8" (261.1 cm)	124" (315 cm)	126.8" (322.1 cm)	148" (376 cm)
Moldboard Height	30" (76 cm)	30" (76 cm)	30" (76 cm)	30" (76 cm)	30" (76 cm)	30" (76 cm)
Moldboard Material	7 gauge steel	11 gauge steel	7 gauge steel	11 gauge steel	7 gauge steel	11 gauge steel
Vertical Support Ribs	4 vertical ribs	6 vertical ribs	4 vertical ribs	8 vertical ribs	4 vertical ribs	10 vertical ribs
Horizontal Supports	2 Horizontal Pans	1 upper pan, 3 lower pans	2 Horizontal Pans	3 upper pans, 5 lower pans	2 Horizontal Pans	3 upper pans, 5 lower pans
Cutting Edge	1-1/2" x 8" (3.8 cm x 20.3 cm) reversible rubber	1/2"x6" (1.3cm x 15cm) Steel	1-1/2" x 8" (3.8 cm x 20.3 cm) reversible rubber	1/2"x6" (1.3cm x 15cm) Steel	1-1/2" x 8" (3.8 cm x 20.3 cm) reversible rubber	1/2"x6" (1.3cm x 15cm) Steel
Tripping base angle	NA	1/2"x3 1/2"x3 1/2" (1cm x 9cm x 9cm)	NA	1/2"x3 1/2"x3 1/2" (1cm x 9cm x 9cm)	NA	1/2"x3 1/2"x3 1/2" (1cm x 9cm x 9cm)
Cutting Edge Bolts	5/8-11 x 3-1/2" Grade 5 carriage bolt (qty 6)	1/2-13 x 1-3/4" Grade 5 carriage bolt (qty 10)	5/8-11 x 3-1/2" Grade 5 carriage bolt (qty 8)	5/8-11 x 2" Grade 5 carriage bolt (qty 12)	1/2-13 x 1-3/4" Grade 5 carriage bolt (qty 10)	5/8-11 x 2" Grade 5 carriage bolt (qty 12)
Attack Angle	70°	70°	70°	70°	70°	70°
BOX WING						
Wing Width	38" (96.5 cm)	38" (96.5 cm)	38" (96.5 cm)	38" (96.5 cm)	38" (96.5 cm)	38" (96.5 cm)
Wing Height	30.375" (77 cm)	30.750" (78.1 cm)	30.375" (77 cm)	30.750" (78.1 cm)	30.375" (77 cm)	30.750" (78.1 cm)
Wing Material	5/16" (0.8 cm)	1/4" (0.6 cm)	1/4" (0.6 cm)	1/4" (0.6 cm)	1/4" (0.6 cm)	1/4" (0.6 cm)
Pivot Pin Diameter	NA	NA	NA	NA	NA	NA
Wing Leveling	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Plow Shoes	Skid Shoes (AR 400)	Skid Shoes (AR 450)	Skid Shoes (AR 400)	Skid Shoes (AR 450)	Skid Shoes (AR 400)	Skid Shoes (AR 450)
Wing Deg. Rotation	NA	NA	NA	NA	NA	NA
TRIP MECHANISM						
Trip Method	Rubber Edge	Trip-Edge	Rubber Edge	Trip-Edge	Rubber Edge	Trip-Edge
Trip Pivot Pin Diameter	NA	1" (25.4 mm)	NA	1" (25.4 mm)	NA	1" (25.4 mm)
Trip Springs	NA	4	NA	4	NA	8
Trip Spring Type	NA	0.375"(9.5mm) Hooked Extension Spring	NA	0.375"(9.5mm) Hooked Extension Spring	NA	0.375"(9.5mm) Hooked Extension Spring
Trip Spring Adjustment	NA	3/4"(19mm) Gr 5 Bolt	NA	3/4"(19mm) Gr 5 Bolt	NA	3/4"(19mm) Gr 5 Bolt
ATTACHMENT						
Connection Method	Universal Coupler	Universal Coupler	Universal Coupler	Universal Coupler	Universal Coupler	Universal Coupler
Vertical Hitch Float	Rigid	Automatic	Rigid	Automatic	Rigid	Automatic
PLOW WEIGHT*						
	860 lb (390 kg)	900 lb (409 kg)	970 lb (440 kg)	1000 lb (455 kg)	1078 lb (489 kg)	1245 lb (565 kg)
WARRANTY						
			Limited 2 Year Parts and Labor			

* Does not include attachment forks.

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

11/25/19 MM