



**TAILGATE SPREADER  
SPECIFICATIONS**

	<b>TGS 300</b>	<b>TGS 600</b>	<b>TGS 800</b>	<b>TGS 1100</b>
<b>HOPPER</b>				
Hopper Design	Low Profile	Low Profile	Low Profile	Low Profile
Hopper Capacity	3 Cubic Feet/200lbs (90.7kg)	6 Cubic Feet/400lbs (181.4kg)	8 Cubic Feet/800lbs (362.9kg) (sand)	11 Cubic Feet/800lbs (362.9kg)
Hopper Dimensions	21-7/8"(55.6cm) x 29"(73.7cm) x 15"(38.1cm)	26"(66cm) x 38"(96.5cm) x 21"(53.3cm)	48"(121.9cm) x 36"(91.4cm) x 21"(53.3cm)	36"(91.4cm) x 44"(111.8cm) x 24"(61cm)
Hopper Material	LLDPE Polyethylene with UV Stabilizer	LLDPE Polyethylene with UV Stabilizer	LLDPE Polyethylene with UV Stabilizer	LLDPE Polyethylene with UV Stabilizer
Hopper Thickness	1/8"(3.2mm)	3/16"(4.8mm)	3/16"(4.8mm)	3/16"(4.8mm)
Hopper Wall Angle	49°	49°	49°	49°
Hopper Cover	Solid Polyethylene	Solid Polyethylene	Solid Polyethylene	Solid Polyethylene
Feed Gate	N/A	Standard	Standard	Standard
Top Screen with Bag Opener	Not Recommended	Standard	Standard	Standard
Vibrator	Not Recommended	Optional	Optional	Optional
<b>SPINNER</b>				
Spinner Diameter	12"(30.5cm)	12"(30.5cm)	12"(30.5cm)	12"(30.5cm)
Spinner Material	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Feed Mechanism	Material Saver System	Internal Auger with Agitator	Paddle Wheel with Agitator	Internal Auger with Agitator
<b>DEFLECTOR</b>				
Deflector Material	Polyethylene	Polyethylene	Polyethylene	Polyethylene
Spread Width	4'(1.2m) - 30'(9.1m)	4'(1.2m) - 30'(9.1m)	4'(1.2m) - 20'(6.1m)	4'(1.2m) - 30'(9.1m)
<b>CONTROLS</b>				
Control Box	Variable Speed Dial, Blast Feature Over Load Protection	Variable Speed Dial, Blast Feature Over Load Protection	Variable Speed Dial, Blast Feature Over Load Protection	Variable Speed Dial, Blast Feature Over Load Protection
<b>POWER UNIT</b>				
Spinner Motor	High-Torque 12 volt	High-Torque 12 volt	High-Torque 12 volt	High-Torque 12 volt
Paddle Wheel Motor	N/A	N/A	High-Torque 12 volt	N/A
<b>ATTACHMENT SYSTEM</b>				
Slide-In Attachment (standard)	Manual Attachment	Manual Attachment	Manual Attachment	Manual Attachment
RT3 Attachment (optional)	N/A	Manual Attachment	Manual Attachment	Manual Attachment
<b>MISCELLANEOUS</b>				
Spreading Material	Fine De-Icer	Dry Salt or De-Icer	Dry Salt, Sand or De-Icer	Dry Salt or De-Icer
<b>SPREADER WEIGHT*</b>				
	70 lb (31.75kg) (Including Mount)	101 lb (45.8kg)	220 lb (99.8kg)	152 lb (68.9kg)
<b>WARRANTY</b>				
	Limited 2 year Parts and Labor	Limited 2 year Parts and Labor	Limited 2 year Parts and Labor	Limited 2 year Parts and Labor

\* Spreader weight does not include attachment weight. Attachment weight range: 30-198 lb.

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

11/22/19 MM