



**DRAG PRO  
SPECIFICATIONS**

**8' Fixed Wing**

**8'-12' Hydraulic Folding Wing**

**8'-16' Hydraulic Folding Wing**

	8' Fixed Wing	8'-12' Hydraulic Folding Wing	8'-16' Hydraulic Folding Wing
<b>MOLDBOARD</b>			
Moldboard Width, Folded	96" (244 cm)	96" (244 cm)	96" (244 cm)
Moldboard Width, Extended	N/A	144" (366 cm)	192" (488 cm)
Moldboard Thickness	11-ga steel	11-ga steel	11-ga steel
Moldboard Height	24" (61 cm)	24" (61 cm)	24" (61 cm)
Moldboard Cutting Edge	1/2" x 6" (1.3 cm x 15 cm), Steel	1/2" x 6" (1.3 cm x 15 cm), Steel	1/2" x 6" (1.3 cm x 15 cm), Steel
Wing Cutting Edges	1-1/2" x 6" (4 cm x 15 cm), Polyurethane	1-1/2" x 6" (4 cm x 15 cm), Polyurethane	1-1/2" x 6" (4 cm x 15 cm), Polyurethane
Wing Cylinders	N/A	Dual Acting, 2-1/4" x 1-1/8" x 5-1/8" (6 cm x 3 cm x 13 cm)	Dual Acting, 2-1/4" x 1-1/8" x 5-1/8" (6 cm x 3 cm x 13 cm)
Lift Cylinder	Dual Acting, 2-1/4" x 1-1/8" x 12" (6 cm x 3 cm x 31 cm)	Dual Acting, 2-1/4" x 1-1/8" x 12" (6 cm x 3 cm x 31 cm)	Dual Acting, 2-1/4" x 1-1/8" x 12" (6 cm x 3 cm x 31 cm)
<b>LIGHTING</b>			
	N/A	N/A	N/A
<b>CONTROLS</b>			
	SmartTouch 2 Hand Held Control	SmartTouch 2 Hand Held Control	SmartTouch 2 Hand Held Control
<b>POWER UNIT</b>			
Construction	Heavy Duty, Cast Iron Pump Housing	Heavy Duty, Cast Iron Pump Housing	Heavy Duty, Cast Iron Pump Housing
Mounting	Plow Mounted with Enclosure Cover	Plow Mounted with Enclosure Cover	Plow Mounted with Enclosure Cover
Reservoir Capacity	2 Quart	2 Quart	2 Quart
Type	Fixed Displacement Gear Pump, 1/8" Wide Gear Face (.065 cu.in/rev)	Fixed Displacement Gear Pump, 1/8" Wide Gear Face (.065 cu.in/rev)	Fixed Displacement Gear Pump, 1/8" Wide Gear Face (.065 cu.in/rev)
Flow Rate	.85 GPM (3.2 LITER/MIN) @ 1500 PSI	.85 GPM (3.2 LITER/MIN) @ 1500 PSI	.85 GPM (3.2 LITER/MIN) @ 1500 PSI
Motor	12 VDC High Torque Motor	12 VDC High Torque Motor	12 VDC High Torque Motor
Amp Draw	125 Amps, 12 VDC, @ 1500 PSI	125 Amps, 12 VDC, @ 1500 PSI	125 Amps, 12 VDC, @ 1500 PSI
Relief Setting	2000 PSI Full Bypass Relief	2000 PSI Full Bypass Relief	2000 PSI Full Bypass Relief
Filtration	100 Mesh Screen on Inlet and Exhaust Tubes	100 Mesh Screen on Inlet and Exhaust Tubes	100 Mesh Screen on Inlet and Exhaust Tubes
<b>PLOW WEIGHT*</b>			
	780 lb (354 kg)	790 lb (358 kg)	890 lb (404 kg)
<b>WARRANTY</b>			
	Limited 2 year Parts and Labor	Limited 2 year Parts and Labor	Limited 2 year Parts and Labor

\* Plow weight does not include mount weight. Vehicle mount weight range: 75-105 lb (34-48 kg).

BOSS Products, a division of The Toro Company reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

11/25/19 MM