



DROP SPREADER SPECIFICATIONS

Exact Path 2.5

Exact Path 6.0

HOPPER

Hopper Capacity	2.5 cu ft (0.07 cu m)	6.0 cu ft (0.17 cu m)
Overall Depth	13-5/8" (35 cm)	16-1/2" (42 cm)
Overall Height	21-3/4" (55 cm) with cover	29-3/4" (76 cm) with cover
Overall Width	47-3/8" (120 cm)	47-3/8" (120 cm)
Hopper Length	12-1/8" (31 cm)	16" (41 cm)
Hopper Width	39-3/8" (100 cm)	39-3/8" (100 cm)
Hopper Material	Stainless Steel	Stainless Steel
Hopper Cover	Poly	Poly
Top Screen with Bag Opener	Standard	Standard
Vibrator	Optional	Optional

SPREADER WEIGHT

Empty	150 lb (68 kg)	175 lb (79.4 kg)
Full	375 lb (@ 90 lb/cu ft)	715 lb (@ 90 lb/cu ft)

FEED SYSTEM

Feed Drum	Stainless Steel	Stainless Steel
Feed Gate	8 Position Manual Adjustment	8 Position Manual Adjustment
Feed Baffle	Poly	Poly

CONTROLS

Control Box	Variable Speed Dial, Blast Feature Over Load Protection	Variable Speed Dial, Blast Feature Over Load Protection
-------------	--	--

MOTOR

Feed Drum	1/4 hp, 12-volt DC	1/4 hp, 12-volt DC
Gearbox Ratio	137.25:1 right angle worm	137.25:1 right angle worm

ATTACHMENT SYSTEMS

UTV Bed Mount	UTV Bed Mount
3-Point Hitch Mount	3-Point Hitch Mount
2' Receiver Mount	2' Receiver Mount

MINIMUM BED CAPACITY

500 lb (226.8 kg)	1,000 lb (453.6 kg)
-------------------	---------------------

MISCELLANEOUS

Spreading Material	Bagged De-Icers / Coarse Bulk Salt	Bagged De-Icers / Coarse Bulk Salt
Spreading Width	40" (102 cm)	40" (102 cm)

WARRANTY

Limited 2 year Parts and Labor	Limited 2 year Parts and Labor
-----------------------------------	-----------------------------------

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

11/22/19 MM